



Power Station Switch Update/Service Information

The following information pertains to all Shopsmith Power Stations. If you have recently purchased or are repairing a Power Station, which contains a Date Code of 11/25/92 or later, please refer to Item #1 below. If you are repairing a Power Station, which contains a Date Code earlier than 11/25/92, please refer to Item #2 below.

The following Part Numbers have changed; please update your Power Station Instruction Manual.

- Ref. No. 36, Part No. 514796, Description - Locking Rocker Switch, Qty 1 SHOULD NOW READ Ref No. 36, Part No. 556090, Description - On/Off Switch, Qty 1. Add 522456 - 3/16" Single Spade Terminal (4)
- 1 Push the four 3/16 single spade terminals on the 1/4" terminals protruding from the switch back. Be sure the two center spade terminals are positioned away from the two bottom switch terminals. Next position the 3/16" spades facing left and right on the two bottom switch terminals. Install the two white wires on the right side of switch and the two black wires on the left.
 - 2 Discard the four 3/16" single spade terminals. You will not need them. Install the two black wires that were removed from your old switch to either right or left side of the switch. In the unlikely event that your switch goes bad again, simply remove the black wires and move them to the opposite side of the switch.

NOTE: If you have further questions or need assistance, please contact Customer Services: Toll Free 1-800-762-7555 (Outside the US please call 937/898-6070 x-376).

